
Deako Simple Ceiling Fan Controller

Quiet fan speed controller



The new Deako fan speed controls enable quiet fan control at any setting. Designed for Single Pole installations, the new fan speed controller is the ideal solutions to upgrade from a standard fan switch offering your homeowners the comfort & convenience and more control capabilities.

Features

- Eliminate need for pull chains
- Combine standard toggle "ON/OFF" switch functionality with a smooth slide for selection of low, medium or high fan speeds.
- Slide up to on/increase, down to decrease
- Use the rocker switch to turn the fan off and on and return to the last speed setting.
- Use only one (1) Fan Speed Control per load.

Applications

- Quiet 1.5-amp fan speed controls are ideal for home offices, bedrooms and any area where ceiling fan noise could become distracting
- For use with multi-speed ceiling fans

deako.

Specifications

Dimensions (H x W x D)1.77" x 1.6" x 3.1"Weight2.4 ozCompatibilitySingle pole circuitsDeako Faceplate DS-FP seriesDeako Backplate DS-BP seriesDeako Backplate DS-BP seriesNeutral wire requiredSupported Currents & Load TypesMax 1.5A ceiling or paddle fan onlyRegulatory ApprovalscULus Listed (UL1917)EnvironmentIndoor use onlyOperating temperature range0°C to 40°C (32°F to 104°F)Warranty1-yearVertical MarketsResidentialMultiple dwellingsHospitality / lodging		
CompatibilitySingle pole circuitsDeako Faceplate DS-FP seriesDeako Backplate DS-BP seriesDeako Backplate DS-BP seriesNeutral wire requiredSupported Currents & Load TypesMax 1.5A ceiling or paddle fan onlyRegulatory ApprovalsCULus Listed (UL1917)EnvironmentIndoor use onlyOperating temperature range0°C to 40°C (32°F to 104°F)ColorWarranty1-yearVertical MarketsResidential Multiple dwellings	Dimensions (H x W x D)	1.77'' x 1.6'' x 3.1''
Deako Faceplate DS-FP seriesDeako Backplate DS-BP seriesDeako Backplate DS-BP seriesNeutral wire requiredSupported Currents & Load TypesMax 1.5A ceiling or paddle fan onlyRegulatory ApprovalsCULus Listed (UL1917)EnvironmentIndoor use onlyOperating temperature range0°C to 40°C (32°F to 104°F)ColorWarranty1-yearVertical MarketsResidential Multiple dwellings	Weight	2.4 oz
Peako Backplate DS-BP series Neutral wire required Supported Currents & Load Max 1.5A ceiling or paddle fan only Types Regulatory Approvals CULus Listed (UL1917) Environment Operating temperature range O°C to 40°C (32°F to 104°F) Color Warranty 1-year Vertical Markets Residential Multiple dwellings	Compatibility	Single pole circuits
Neutral wire required Supported Currents & Load Max 1.5A ceiling or paddle fan only Regulatory Approvals cULus Listed (UL1917) Environment Indoor use only Operating temperature range 0°C to 40°C (32°F to 104°F) Color White Vertical Markets Residential Multiple dwellings		Deako Faceplate DS-FP series
Supported Currents & Load TypesMax 1.5A ceiling or paddle fan onlyRegulatory ApprovalscULus Listed (UL1917)EnvironmentIndoor use onlyOperating temperature range0°C to 40°C (32°F to 104°F)ColorWhiteWarranty1-yearVertical MarketsResidentialMultiple dwellings		Deako Backplate DS-BP series
TypesCurrent of the second		Neutral wire required
EnvironmentIndoor use onlyOperating temperature range0°C to 40°C (32°F to 104°F)ColorWhiteWarranty1-yearVertical MarketsResidentialMultiple dwellings		Max 1.5A ceiling or paddle fan only
Operating temperature range 0°C to 40°C (32°F to 104°F) Color White Warranty 1-year Vertical Markets Residential Multiple dwellings	Regulatory Approvals	cULus Listed (UL1917)
Color White Warranty 1-year Vertical Markets Residential Multiple dwellings	Environment	Indoor use only
Warranty 1-year Vertical Markets Residential Multiple dwellings	Operating temperature range	0°C to 40°C (32°F to 104°F)
Vertical Markets Residential Multiple dwellings	Color	White
Multiple dwellings	Warranty	1-year
	Vertical Markets	Residential
Hospitality / lodging		Multiple dwellings
		Hospitality / lodging

Also Available in the Deako Switch Family

- Simple Motion Switch
- Simple Dimmer
- Smart Switch
- Smart Dimmer
- Smart Scene Controller Switch
- Smart Scene Controller Dimmer
- Smart Plug

Date	Notes
Job location	
Approved by	
Job no. / type	